

Micro Sprinklers

FEATURES and BENEFITS

- The Strong “C” frame design allows for excellent water distribution uniformity.
- During rotation the spinner is supported between two bearings.
- The spinner on the inverted model has a cover that protects the bottom bearing from dust.
- Four Orbita micro sprinkler models available: Standard, Inverted, Adjustable and Spike.
- Six colour coded bases to choose from for the Standard model.
- Four colour coded bases for the Inverted model.
- Base colour identifies the flow rate.
- Two Adjustable models available:
 1. **Black Base** with a **Black Rotor**
 2. **Yellow Base** with a **Blue Rotor**.
- The Spike is a pre-assembled model for quick and easy installation with a **Red Base**, an adjustable rotor for flow and throw control, 500 mm flexible tube and 4.5 mm Joiner. There are two spike lengths to choose from, 200 mm and 310 mm.

APPLICATIONS

- Ideal for large areas that include garden beds, landscapes, vegetable gardens and agricultural applications.



Standard



Inverted



Adjustable



Orbita Micro Sprinklers															
		STANDARD						INVERTED				ADJUSTABLE		SPIKE	
		Brown	Blue	Green	Red	Orange	Grey	Brown	Blue	Green	Red	Black	Yellow	Red	Red
		0.9 mm	1.0 mm	1.3 mm	1.5 mm	1.8 mm	2.0 mm	0.9 mm	1.0 mm	1.3 mm	1.5 mm	1.5 mm	1.5 mm	1.5 mm	1.5 mm
PACKAGING															
Order Codes	Packs	201035	201045	201055	201065	201075	201085	201105	201115	201125	201135	201394	201404	201552	201562
	Bulk	020103	020104	020105	020106	020107	020108	020110	020111	020112	020113	020139	020140	020155	020156
Quantity per Bag	Packs	50						50				25	10	10	
	Bulk	500						500				500	200	150	
Bags per Carton	Packs	120						120				100	20	15	
	Bulk	12						12				5	1	1	
Weight per Carton (kg)	Packs	15.5						15.6				12.1	9.9	8.6	
	Bulk	15.0						15.1				11.5	9.6	8.4	
Base Inlet Connection		"FAST" Thread						"FAST" Thread				10-32 UNF Thread		4.5 mm Barb	
Dimensions	Height	41 mm						41 mm				53 mm	415 mm	525 mm	
	Width	33 mm						33 mm				33 mm	33 mm	33 mm	
Assembled	Depth	12 mm						12 mm				23 mm	23 mm	23 mm	
	Weight	2.3 g						2.3 g				4.0 g	43.5 g	47.1 g	
Material		U.V. Stabilized													